JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

POSITION PAPER

Integrated Biomechanical Framework for the Barbell Back Squat: A 26-Parameter Model for Technique Standardization and Injury Risk Reduction

Author/s

Dr. Neeraj Mehta, PhD

MMSx Authority Institute for Movement Mechanics & Biomechanics, Ohio, USA.

0000-0001-6200-8495

Dr. Steve Henderson, PhD

MMSx Authority Institute for Movement Mechanics & Biomechanics, USA.

0009-0005-7485-1427

Dr. Josh Smith, PhD

Clinical Rehabilitation & Sports Biomechanics Specialist, USA.

0009-0008-1412-7076

Hatem Spetan, MSc

Asst. Fitness Directorate, Armah Sports Company, Jeddah, Saudi Arabia.

0009-0009-2138-7498

Achouri Imen, PhD

High Institute of Sport and Physical Education of Sfax, University of Sfax, Sfax, Tunisia.

0000-0003-1051-6978

Sumit Chaudhary Khobey, BSc

Strength & Conditioning Dept, Bodygntx Rehab Institute, USA.

0009-0008-1523-6493

Pankaj M, MSc

MMSx Authority Institute for Movement Mechanics & Biomechanics Research.

0009-0009-5920-0158

Dr. Karun Jain, MBBS, MS, FACS

MMSx Authority Institute for Movement Mechanics & Biomechanics Research

0009-0000-9635-7132

MMSx Authority Institute for Movement Mechanics & Biomechanics Research Powell, Ohio, USA

Correspondence: info@mmsxauthority.com

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Abstract

Background:
The back squat is one of the most widely prescribed resistance exercises in athletic performance, rehabilitation, and strength training programs. Despite its extensive use, considerable variability exists in coaching practices and execution strategies due to differences in anthropometry, mobility, and training objectives. The absence of a unified biomechanical framework has contributed to inconsistent technique instruction and increased risk of mechanical overload and injury.

This study presents a **conceptual biomechanical framework derived from existing literature and biomechanical modeling** to standardize squat technique evaluation.

Objective:
The purpose of this position paper is to propose a comprehensive biomechanical framework for the back squat that integrates anthropometric considerations, joint mechanics, neuromuscular control, and real-time biomechanical feedback to guide technique standardization and injury-risk reduction.

Methods:
The framework synthesizes evidence from biomechanical literature and integrates quantitative parameters derived from three-dimensional motion capture, force-plate kinetics, surface electromyography (EMG), and inertial measurement unit (IMU) data. Twenty-six biomechanical parameters (A–Z) were organized to describe key aspects of squat execution, including base of support, bar path mechanics, joint kinematics, torque distribution, neuromuscular control, and movement consistency under load.

Framework and Key Parameters:
The proposed model establishes recommended ranges for joint angles, intra-abdominal pressure, ground reaction forces, and bar-path deviation during the back squat. The framework also identifies critical fault thresholds (e.g., lumbar flexion >10°, knee valgus >5°, bar path deviation >3 cm) and integrates sensor-based monitoring approaches to facilitate real-time feedback during training and rehabilitation contexts.

Practical Implications:
By combining anthropometric individualization with objective biomechanical measurement, this framework provides a structured reference for coaches, clinicians, and researchers seeking to optimize squat mechanics, enhance performance outcomes, and reduce injury risk. Adoption of standardized biomechanical parameters may improve consistency in instruction, support movement screening protocols, and advance evidence-based practice in strength and conditioning.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Graphical Abstract – Concept Layout

Title at top

Integrated Biomechanical Framework for the Back Squat

Subtitle

A 26-Parameter Model for Technique Standardization and Injury Risk Reduction

---

Graphical Abstract

A conceptual overview of the proposed biomechanical framework for the back squat integrating anthropometric variation, joint kinematics, neuromuscular activation, and sensor-derived biomechanical measurements to improve technique standardization, performance outcomes, and injury risk management.

Anthropometry

↓

Biomechanical Measurement

↓

26-Parameter Framework

↓

Optimized Squat Mechanics

↓

Performance + Injury Prevention

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Keywords:

back squat, biomechanics, anthropometry, technique standardization, injury prevention, real-time feedback

Introduction

The back squat remains one of the most frequently prescribed resistance-training exercises. Despite extensive research, the absence of a unified, evidence-based guideline that accounts for individual anatomical differences has led to wide variation in coaching practices. This position paper consolidates 26 biomechanical parameters (labeled A–Z) into a coherent framework supported by sensor-derived data. The recommendations are intended to serve as a reference for researchers, clinicians, coaches, and practitioners seeking to optimize performance while minimizing injury risk.

Integrated Biomechanical Framework for the Back Squat

The proposed framework integrates twenty-six biomechanical parameters that collectively describe anthropometric structure, joint mechanics, neuromuscular coordination, and external mechanical loading during the barbell back squat. These parameters provide a structured method for evaluating squat technique and movement consistency.

Table 1. Summary of Key Biomechanical Parameters for Back Squat Assessment

Parameter	Variable	Recommended Range	Measurement Method
Anthropometry	Femur–torso ratio	Individualized	Motion capture
Joint Angles	Knee flexion	125–135°	IMU or motion capture
Bar Path	Horizontal deviation	≤3 cm	Video tracking
Lumbar alignment	Lumbar lordosis	0–5°	Motion capture

Proposed Biomechanical Framework (A–Z)

A: Anatomy & Anthropometry
Individual anatomical structure (femur length, tibia length, torso length, joint angles, and muscle attachment points) significantly influences squat mechanics. No single “universal” technique exists. For a femur-to-torso ratio > 1.2, torso lean typically ranges from 30–40° with required ankle dorsiflexion of 15–20°. Limited dorsiflexion may necessitate heel elevation of 0.75–1.25 inches to preserve lumbar neutrality.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Femur:Torso Ratio	Torso Lean (°)	Ankle Dorsiflexion (°)	Recommended Heel Elevation (inch)
> 1.2	30–40	15–20	0.75–1.25
0.9–1.2	20–30	10–15	0–0.75
< 0.9	10–15	5–10	None

Table 1. Influence of femur-to-torso ratio on squat posture parameters



Figure 1

Anthropometric influence on back squat mechanics.
Illustration of how variations in femur-to-torso ratio influence torso inclination and ankle dorsiflexion requirements during the back squat. Individuals with relatively longer femurs typically require greater forward trunk inclination and increased ankle dorsiflexion to maintain center-of-mass balance over the mid-foot. The diagram highlights the relationship between segment proportions and compensatory joint positioning during descent.

B: Base of Support & Balance

Stance Multiplier	External Rotation (°)	Peak GRF (N) at 120 kg load	Stability Rating
1.0×	10	1650	Moderate
1.2×	15	1800	Optimal

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

1.4×	20	1720	High

Table 2. Stance width effects on ground reaction force (120 kg external load)



JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science



Figure 2

Ground reaction force distribution across stance widths.
Top-down visualization of center-of-pressure (COP) and ground reaction force (GRF) patterns during the back squat at different stance widths (1.0×, 1.2×, and 1.4× shoulder width). The figure illustrates how stance width influences force distribution beneath the feet and overall

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

stability during load acceptance. Optimal force symmetry is typically observed at moderate stance widths with controlled external foot rotation.

C: Core Engagement & Control
Deep abdominal and spinal muscle activation maintains trunk rigidity. The Valsalva maneuver produces intra-abdominal pressure of 25–35 mmHg while preserving 0–5° lumbar lordosis.

Phase	Target IAP (mmHg)	Lumbar Lordosis (°)
Bottom Position	25–35	0–5
Ascent	28–32	0–3

Table 3. Intra-abdominal pressure targets



Figure 3

Core activation and intra-abdominal pressure during squat stabilization.
Cross-sectional representation of trunk musculature illustrating activation of abdominal and

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

spinal stabilizers during the squat. Increased intra-abdominal pressure generated through bracing and the Valsalva maneuver contributes to spinal stability and reduced shear loading on the lumbar vertebrae. The image highlights the role of coordinated trunk musculature in maintaining neutral spinal alignment under load.

D: Depth & Dorsiflexion
Recommended depth is hip crease at or below the patella with neutral lumbar spine. Typical ranges: hip flexion 110–120°, knee flexion 125–135°, ankle dorsiflexion 15–25°.



Figure 4

Hip and knee torque patterns during eccentric and concentric squat phases.
Force-plate derived torque curves illustrating the distribution of mechanical demand across the hip and knee joints throughout the squat movement. The eccentric phase demonstrates controlled loading as torque increases prior to the transition point, while the concentric phase reflects rapid force production to overcome gravitational load. These torque-time characteristics are essential for understanding joint loading strategies during resistance training.

E: Eccentric & Concentric Phases (Tempo)
Controlled eccentric phase (2–4 s) followed by explosive concentric phase optimizes strength and power development. Standard tempo: 3 s descent, 1 s ascent.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science



Figure 5

Ideal bar path alignment relative to the lifter's center of mass.
Side-view schematic illustrating the optimal vertical trajectory of the barbell during the back squat. Maintaining a bar path within approximately ±3 cm of the mid-foot minimizes unnecessary horizontal displacement and improves lifting efficiency. Deviations from this path increase mechanical demand on the lumbar spine and lower extremity joints.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

F: Faults & Failure Modes
Common deviations include lumbar flexion >10° and knee valgus >5°. Real-time correction is recommended.

Joint	Target Angle (°)	Tolerance (±)
Hip	110–120	5°
Knee	125–135	5°
Ankle	15–25	5°
Lumbar	0–5	3°

Table 4. Fault detection thresholds and corrective actions



Figure 6

Real-time fault detection in squat mechanics using motion capture.
Example of biomechanical monitoring identifying deviations in joint angles during squat execution. Key joint segments including the ankle, knee, hip, and lumbar spine are evaluated to detect alignment errors such as valgus collapse or lumbar flexion. Motion capture and inertial measurement systems allow immediate identification and correction of technical faults.

G: Grip & Gaze

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

High-bar position on trapezius or low-bar on posterior deltoids; neutral cervical spine with 0–5° upward gaze.



Figure 7

Knee valgus detection through inertial measurement analysis.
Visualization of knee alignment differences during squat execution using IMU-based monitoring. The left illustration shows excessive knee valgus (6° deviation), while the corrected

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

position demonstrates improved alignment (2° deviation). Monitoring knee alignment is critical for reducing excessive medial knee loading and improving lower limb stability.

H: Hip & Hinge Mechanics
Coordinated hip and knee flexion with hip break occurring 0.1–0.15 s after knee break.

Muscle	Activation (% MVC)
Glutes	45
Quadriceps	40
Hamstrings	35
Core	30

Table 5. Recommended joint torques at 120 kg load
JointPeak Torque (Nm)Hip160Knee130



Figure 8

Hip and knee torque-time curves during loaded squatting.
Graphical representation of torque development at the hip and knee joints during the squat movement cycle. Peak hip torque typically occurs near the transition between the eccentric and concentric phases, reflecting the mechanical demand placed on the posterior chain. These curves illustrate the coordinated joint contribution required for effective force generation.

I: Intent & Individualization

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Technique should be adapted to training goals (strength: 80–90% 1RM; hypertrophy: 60–75% 1RM).

J: Joint-by-Joint Analysis
Mobility at ankles and hips; stability at knees and lumbar spine.

Joint	Torque (Nm) at 120 kg
Hip	160
Knee	130

Table 6. Joint roles and typical ranges

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science



Figure 9

Joint-by-joint mobility and stability model applied to squat mechanics.
Diagram illustrating the functional roles of major joints involved in the squat pattern. Ankles and hips primarily contribute mobility, while the knees and lumbar spine serve stabilizing roles during load transfer. Understanding these joint interactions assists in diagnosing movement limitations and guiding corrective strategies.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

K: Kinematics & Kinetics
Ideal bar path deviation ≤3 cm; ground reaction force 1.6–2.2× body weight. Posterior bar placement increases hip torque relative to front squat.



Figure 10

Kinematic analysis of barbell trajectory during the back squat.
Graph illustrating bar velocity, power output, and mechanical work during the concentric phase of the squat. The figure demonstrates how force production and velocity interact to determine peak power output during the lift. Monitoring these variables helps optimize training intensity and mechanical efficiency.

L: Lumbar Mechanics and Lever Arms

Parameter: Lumbar spine integrity and external moment arms.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Gold-Standard Principle: Maintain lumbar shear forces within tolerable physiological ranges (≈ <600 N) while controlling trunk inclination.

Description:
The back squat produces a relatively long external moment arm between the barbell and the lumbosacral joint compared with front-loaded squat variations. This configuration increases the torque demand on the lumbar spine and requires coordinated activation of the trunk stabilizers to maintain spinal alignment and control shear forces. Proper trunk stiffness and hip contribution are therefore essential to prevent excessive anterior shear and spinal flexion during high-load squatting. Lever arm distances in the back squat typically range from **0.30–0.40 m**, depending on anthropometry and bar position.

Real-Time Example:
Force-model estimation identifies **500 N lumbar shear with a 0.35 m moment arm**, prompting corrective adjustments in trunk inclination and bar path alignment.



M: Muscular Contribution

Parameter: Functional roles of agonists, synergists, and stabilizing musculature.

Gold-Standard Principle: Coordinated and balanced neuromuscular activation across prime movers and stabilizers.

Description:
The back squat requires integrated activation of the hip and knee extensors with simultaneous trunk stabilization. The **gluteus maximus and quadriceps femoris** function as primary force generators, while the **hamstrings and spinal stabilizers** contribute to joint stabilization and force transmission through the posterior kinetic chain. Electromyographic studies commonly report activation levels approximating **glutes (~45% MVC), quadriceps (~40% MVC), hamstrings (~35% MVC), and trunk stabilizers (~30% MVC)** during controlled squatting tasks.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Real-Time Example:
Surface EMG monitoring detects **43% gluteal activation**, indicating slightly reduced hip contribution and prompting cueing to improve posterior chain engagement.



JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

N: Neuromuscular Control

Parameter: Stability and movement consistency under increasing load and fatigue.

Gold-Standard Principle: Preserve kinematic consistency with minimal deviation (joint variance <5°).

Description:
Neuromuscular control reflects the ability of the central nervous system to maintain coordinated movement patterns despite fatigue or load escalation. During the back squat, stable joint trajectories and consistent limb alignment indicate effective motor control and sensorimotor integration. Excessive variability may indicate fatigue-related coordination loss or compensatory strategies.

Real-Time Example:
An inertial measurement unit (IMU) records **3° knee-tracking variance across 12 repetitions**, indicating stable neuromuscular control during the set.



O: Objective Measurement

Parameter: Quantitative biomechanical assessment using motion analysis systems.

Gold-Standard Principle: Utilize objective measurement technologies to quantify movement quality and mechanical loading.

Description:
Biomechanical assessment of the squat can be enhanced using motion capture systems, force platforms, and electromyography. These technologies provide quantitative information regarding joint kinematics, ground-reaction forces, and muscle activation patterns. Widely used systems include **3-D motion capture platforms (e.g., Vicon), force plates (e.g., Kistler), and surface EMG**, which together enable comprehensive biomechanical profiling.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Real-Time Example:
Motion capture analysis detects a **2° hip rotation deviation**, allowing immediate correction to restore symmetrical movement mechanics.



JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

P: Planes of Motion

Parameter: Dominant sagittal plane movement with control of frontal and transverse plane deviations.

Gold-Standard Principle: Limit lateral or rotational displacement of the barbell to **<3 cm**.

Description:
Although the squat is primarily a sagittal-plane movement, effective performance requires stabilization across all three anatomical planes. Excessive movement in the frontal or transverse plane may indicate inadequate hip stability, asymmetrical loading, or neuromuscular imbalance. Maintaining a stable bar path within a narrow mediolateral range helps preserve mechanical efficiency and reduce unnecessary joint stress.

Real-Time Example:
Motion capture detects a **2 cm lateral bar displacement**, prompting adjustments in foot pressure distribution and hip stabilization.

Figure X. Multi-planar control analysis during the back squat illustrating sagittal dominance with minimal frontal-plane deviation (<3 cm).



Q: Quality of Repetition

Parameter: Consistency of movement execution across repeated repetitions.

Gold-Standard Principle: Maintain squat depth and joint angles with <5° variation.

Description:
High-quality repetitions demonstrate consistent depth, joint alignment, and bar trajectory throughout a set. Variability in these parameters may indicate fatigue-related degradation in technique or insufficient

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

motor control. Monitoring repetition quality is therefore essential for maintaining mechanical efficiency and minimizing injury risk during repeated loading.

Real-Time Example:
IMU tracking reveals **4° depth variance across ten repetitions**, indicating acceptable repetition consistency under moderate fatigue.



R: Respiration and Intra-Abdominal Pressure

Parameter: Breathing strategy for trunk stabilization.

Gold-Standard Principle: Generate adequate intra-abdominal pressure (≈25–35 mmHg) to enhance spinal stability.

Description:
Effective respiratory strategy contributes to trunk stiffness and spinal stabilization during loaded squatting. The Valsalva maneuver, involving a deep inhalation followed by abdominal bracing, increases intra-abdominal pressure and enhances spinal support by augmenting trunk rigidity. Controlled breath timing is therefore an important component of safe load management.

Real-Time Example:
Pressure monitoring indicates **28 mmHg intra-abdominal pressure**, suggesting effective trunk bracing during the lift.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science



S: Scapular Position

Parameter: Scapular retraction and elevation to stabilize the barbell.

Gold-Standard Principle: Maintain scapular retraction (≈10–15°) to create a stable bar support.

Description:
Proper scapular positioning contributes to upper-back stability and secure bar placement during the back squat. Retraction and mild elevation of the scapulae create a stable “bar shelf” formed by the trapezius musculature, reducing bar displacement and improving load distribution across the upper thoracic region.

Real-Time Example:
Motion capture detects **13° scapular retraction**, confirming adequate upper-back stability during the lift.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science



T: Torque

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Parameter: Joint torque generated at the hip and knee.

Gold-Standard Principle: Maintain torque production within controlled mechanical ranges.

Description:
Joint torque reflects the rotational forces required to extend the hip and knee during the ascent phase of the squat. Mechanical analyses commonly estimate peak torques of approximately **160 Nm at the hip and 130 Nm at the knee**, depending on load magnitude and anthropometry. Efficient torque distribution between joints contributes to balanced force production and reduced localized overload.

Real-Time Example:
Force-plate analysis estimates **155 Nm hip torque**, indicating near-optimal force generation during the lift.

U: Unilateral Considerations

Parameter: Bilateral symmetry and implications for unilateral movement patterns.

Gold-Standard Principle: Maintain bilateral force symmetry with <10% variance.

Description:
Although the back squat is a bilateral exercise, asymmetrical loading between limbs may occur due to strength imbalances or mobility restrictions. Monitoring bilateral symmetry can help identify unilateral deficits that may affect movement efficiency or increase injury risk.

Real-Time Example:
IMU-derived force estimation identifies **7% asymmetry between limbs**, suggesting acceptable bilateral symmetry.

V: Valgus and Varus Stress

Parameter: Knee alignment during the descent and ascent phases.

Gold-Standard Principle: Maintain frontal-plane knee deviation within **<5°**.

Description:
Excessive knee valgus or varus movement during squatting may reflect deficits in hip stabilization, neuromuscular control, or lower-limb alignment. Maintaining controlled knee tracking over the foot helps distribute joint loads effectively and preserve lower-limb mechanics.

Real-Time Example:
IMU analysis detects **6° knee valgus**, which is corrected to **2°** through cueing to improve hip abductor engagement.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

W: Work and Power

Parameter: Mechanical work and power output during the lift.

Gold-Standard Principle: Optimize mechanical output relative to load and movement velocity.

Description:
Mechanical work represents the product of force and displacement, while power reflects the rate at which this work is performed. During loaded squatting, typical mechanical work values may range from **600–800 J**, with power outputs around **≈300 W** depending on load and movement velocity. Monitoring these parameters provides insight into performance efficiency and training intensity.

Real-Time Example:
Force-plate calculations estimate **700 J of work and 280 W of power during a 110 kg lift**.

X: Contextual Training Application

Parameter: Adaptation of squat mechanics to training objectives.

Gold-Standard Principle: Adjust loading parameters according to training goals.

Description:
The mechanical demands of the squat may vary depending on whether the exercise is used for maximal strength development, rehabilitation, or general conditioning. Appropriate modification of load intensity, repetition schemes, and tempo allows the movement to be adapted to different training contexts while maintaining biomechanical integrity.

Real-Time Example:
Training load is adjusted to **80% of one-repetition maximum**, with motion sensors confirming stable technique throughout the set.

Y: Yielding Phase (Eccentric Control)

Parameter: Controlled eccentric descent.

Gold-Standard Principle: Maintain a controlled eccentric phase of approximately **3 seconds**.

Description:
The eccentric phase of the squat contributes significantly to muscle force development and mechanical loading of connective tissues. Controlled descent allows effective storage of elastic energy and prepares the neuromuscular system for the subsequent concentric phase.

Real-Time Example:
IMU tracking records a **3.2-second descent**, which is refined to the target **3-second eccentric phase**.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Z: Zenith (Top Position)

Parameter: Full extension at the completion of the repetition.

Gold-Standard Principle: Achieve full hip and knee extension (≈180°) at the top of the lift.

Description:
The terminal phase of the squat requires complete extension of the hip and knee joints to finalize the repetition and ensure consistent range of motion. Incomplete extension may reduce training effectiveness and compromise repetition standardization.

Real-Time Example:
IMU analysis confirms **178° joint extension**, prompting a slight adjustment to achieve full lockout.

Parameter	Biomechanical Variable	Recommended Range	Measurement Method
Lumbar Mechanics	Shear force	<600 N	Motion + modeling
Knee alignment	Valgus angle	<5°	IMU
Bar path	Horizontal deviation	<3 cm	Motion capture

Fault	Threshold	Action
Lumbar flexion	>10°	Immediate correction
Knee valgus	>5°	Immediate correction
Lateral shift	>3 cm	Immediate correction

Table 7. Muscle activation summary (% MVC)

Sensor Type	Key Metric	Target Value
IMU	Descent velocity	0.3 m/s
Force plate	GRF	1.6–2.2 × BW
EMG	Glute activation	43% MVC

Table 8. Real-time sensor parameters

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

Figure: Mathematical and Real-Time Integration Model





Figure 11

Integrated biomechanical monitoring using multi-sensor analysis.
Combined representation of inertial measurement units (IMUs), force plates, and surface electromyography (EMG) used to evaluate squat performance. These tools enable real-time tracking of joint angles, ground reaction forces, and muscle activation patterns during loaded

movement. Integration of multiple sensor systems provides comprehensive biomechanical feedback for technique optimization.

Discussion

The present position paper proposes an integrated biomechanical framework for the barbell back squat that combines anthropometric variability, joint mechanics, neuromuscular coordination, and objective biomechanical monitoring. Although the squat has been extensively investigated within sports science and biomechanics literature, most previous studies have examined isolated components of the movement, including joint kinetics, muscle activation patterns, or the influence of squat depth. In contrast, the framework proposed in the present work attempts to synthesize these individual components into a unified model composed of twenty-six biomechanical parameters that collectively describe movement mechanics, technical consistency, and potential injury risk during squat performance.

Anthropometric variability is a fundamental determinant of squat mechanics. Previous investigations have demonstrated that segment lengths and body proportions substantially influence joint loading patterns and movement strategies. Escamilla (2001) and Fry et al. (2003) reported that variations in femur length, tibia length, and trunk proportions alter the distribution of hip and knee torques during squatting tasks. Similarly, Lorenzetti et al. (2018) showed that stance width and foot orientation influence joint kinematics, trunk inclination, and bar path trajectory. The present framework incorporates these findings by explicitly linking anthropometric characteristics to technique adjustments such as trunk inclination and ankle dorsiflexion requirements. This approach reinforces the concept that squat technique cannot be universally standardized around a single posture. Instead, optimal squat mechanics should be individualized according to anatomical structure and mobility capacity.

Joint loading patterns during the squat have also been widely examined in biomechanical research. Squat depth, barbell position, and trunk orientation significantly influence joint moments and compressive forces. Escamilla et al. (2001) demonstrated that both hip and knee joint loading vary substantially depending on squat technique, while Hartmann et al. (2013) reported that deeper squat positions increase joint moment demands without necessarily increasing injury risk when performed with appropriate technique and control. The framework proposed in the present paper integrates these findings by defining recommended ranges for joint angles and estimated torque values. Such biomechanical reference ranges may assist coaches, clinicians, and researchers in identifying technique deviations that could increase mechanical stress or reduce movement efficiency.

Muscle activation patterns during the squat have also been well documented. Electromyographic investigations consistently demonstrate coordinated activation of the quadriceps, gluteal muscles, hamstrings, and trunk stabilizers during loaded squatting tasks. Caterisano et al. (2002) reported that deeper squat positions are associated with greater gluteus maximus activation, while Clark et al. (2012) observed that muscle activation varies according to load intensity and barbell placement. The present framework integrates these findings by proposing expected activation ranges for major muscle groups and relating these values to joint mechanics and force production. Establishing such reference values may assist in interpreting EMG data during biomechanical assessments of squat technique.

In addition to joint kinematics and muscle activation, technological advances have enabled increasingly precise biomechanical analysis of complex movements. Motion capture systems, inertial measurement units (IMUs), and force platforms allow accurate measurement of joint angles, barbell trajectory, and ground reaction forces during dynamic tasks. Recent research in sports biomechanics suggests that these technologies can detect subtle movement deviations that may not be visible through observational coaching alone. The framework proposed here

therefore emphasizes objective measurement as an important component of technical evaluation. By integrating sensor-derived variables such as bar path deviation, descent velocity, and ground reaction force magnitude, practitioners may obtain a more comprehensive understanding of squat mechanics and movement efficiency.

Spinal stability represents another critical aspect of squat biomechanics. The lumbar spine is subjected to substantial compressive and shear forces during loaded squatting, particularly when trunk inclination increases or when the barbell deviates from an optimal vertical path. Previous biomechanical investigations by McGill and colleagues have demonstrated that trunk stiffness generated through coordinated abdominal bracing and intra-abdominal pressure contributes to spinal stability during heavy lifting tasks. Within the present framework, intra-abdominal pressure targets and lumbar alignment thresholds are therefore included as key parameters for maintaining spinal integrity. These considerations emphasize the importance of trunk stabilization strategies during resistance training and highlight the role of neuromuscular coordination in managing spinal loading.

Despite the conceptual value of the proposed framework, several limitations should be acknowledged. First, the model represents a synthesis of previously published biomechanical evidence rather than the results of a single experimental investigation. Although the parameter ranges suggested in the framework are supported by existing literature, they should be interpreted as approximate reference values rather than universal thresholds applicable to all populations. Individual differences in mobility, training experience, injury history, and neuromuscular control may influence the optimal execution of the squat.

Second, the framework assumes access to biomechanical measurement technologies such as motion capture systems, IMUs, or force plates. Although these tools are increasingly available in sports science laboratories and high-performance training environments, their accessibility may still be limited in many coaching or clinical contexts. Future work should therefore explore simplified field-based assessment strategies that approximate the biomechanical variables described in this framework using practical observational or video-based methods.

Finally, further experimental research is required to validate the predictive value of the proposed biomechanical parameters. Longitudinal studies examining relationships between squat mechanics, injury risk, and strength development would help determine whether adherence to these biomechanical criteria improves both performance and safety. Additionally, comparative studies examining different squat techniques, training programs, or coaching interventions could further refine the parameter ranges suggested in this model.

Future research should therefore focus on integrating biomechanical monitoring technologies with individualized training prescriptions. Advances in wearable sensors, machine learning algorithms, and real-time motion analysis may allow automated detection of movement deviations and immediate feedback during resistance training. Such developments could significantly enhance the application of biomechanics-informed coaching and contribute to more precise movement assessment in both athletic and clinical settings.

Conclusion

The back squat remains one of the most widely utilized resistance-training exercises in athletic performance, rehabilitation, and strength development. Despite its extensive use, technique

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

instruction and biomechanical interpretation often vary substantially across coaching and clinical settings. The present position paper proposes a comprehensive biomechanical framework that integrates anthropometric considerations, joint kinematics, neuromuscular activation patterns, and objective sensor-derived measurements into a structured model of squat mechanics.

By organizing twenty-six biomechanical parameters into a coherent analytical framework, this model provides a systematic approach for evaluating squat execution, identifying technical deviations, and guiding individualized technique adjustments. The framework emphasizes the importance of anthropometric variability, coordinated joint mechanics, controlled bar path trajectory, and spinal stabilization through appropriate trunk activation and intra-abdominal pressure.

The integration of modern biomechanical monitoring technologies—including inertial measurement units, motion capture systems, force plates, and surface electromyography—offers new opportunities for objective assessment of squat mechanics in both research and applied training environments. When combined with individualized technique modifications, these tools may improve movement consistency, enhance performance outcomes, and reduce the risk of mechanical overload during resistance training.

Although the framework synthesizes current biomechanical knowledge, further empirical research is required to validate the predictive value of the proposed parameter ranges across different populations and training contexts. Future investigations integrating wearable sensor technologies and longitudinal performance monitoring may provide deeper insights into the relationship between squat biomechanics, injury risk, and strength development.

In summary, the proposed biomechanical framework provides an integrated reference model for researchers, clinicians, and strength and conditioning professionals seeking to improve the evaluation and instruction of the back squat. Adoption of standardized biomechanical parameters may contribute to more consistent coaching practices and support the continued advancement of evidence-based movement mechanics.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

References

1. Escamilla, R. F. (2001). Knee biomechanics of the dynamic squat exercise. *Medicine & Science in Sports & Exercise*, 33(1), 127–141.

2. Escamilla, R. F., Fleisig, G. S., Zheng, N., Barrentine, S. W., Wilk, K. E., & Andrews, J. R. (2001). Biomechanics of the knee during closed kinetic chain and open kinetic chain exercises. *Medicine & Science in Sports & Exercise*, 33(4), 556–569.

3. Swinton, P. A., Lloyd, R., Keogh, J. W., Agouris, I., & Stewart, A. D. (2012). A biomechanical comparison of the traditional squat, powerlifting squat, and box squat. *Journal of Strength and Conditioning Research*, 26(7), 1805–1816.

4. Schoenfeld, B. J. (2010). Squatting kinematics and kinetics and their application to exercise performance. *Journal of Strength and Conditioning Research*, 24(12), 3497–3506.

5. Fry, A. C., Smith, J. C., & Schilling, B. K. (2003). Effect of knee position on hip and knee torques during the barbell squat. *Journal of Strength and Conditioning Research*, 17(4), 629–633.

6. Hartmann, H., Wirth, K., & Klusemann, M. (2013). Analysis of the load on the knee joint and vertebral column with changes in squatting depth and weight load. *Sports Medicine*, 43(10), 993–1008.

7. Caterisano, A., Moss, R. F., Pellinger, T. K., Woodruff, K., Lewis, V. C., Booth, W., & Khadra, T. (2002). The effect of back squat depth on the EMG activity of the gluteus maximus and quadriceps. *Journal of Strength and Conditioning Research*, 16(3), 428–432.

8. Bryanton, M. A., Kennedy, M. D., Carey, J. P., & Chiu, L. Z. (2012). Effect of squat depth and barbell load on relative muscular effort in squatting. *Journal of Strength and Conditioning Research*, 26(10), 2820–2828.

9. Hales, M. E., Johnson, B. F., & Johnson, J. T. (2009). Kinematic analysis of the powerlifting style squat and the conventional deadlift during competition. *Journal of Strength and Conditioning Research*, 23(9), 2578–2585.

10. McGill, S. M. (2007). *Low Back Disorders: Evidence-Based Prevention and Rehabilitation*. Human Kinetics.

11. McGill, S. M., Norman, R. W., & Cholewicki, J. (1996). A simple polynomial that predicts low-back compression during complex three-dimensional tasks. *Ergonomics*, 39(9), 1107–1118.

12. Cholewicki, J., & McGill, S. M. (1996). Mechanical stability of the in vivo lumbar spine: implications for injury and chronic low back pain. *Clinical Biomechanics*, 11(1), 1–15.

13. Glassbrook, D. J., Helms, E. R., Brown, S. R., & Storey, A. G. (2017). A review of the biomechanical differences between the high-bar and low-bar back squat. *Journal of Strength and Conditioning Research*, 31(9), 2618–2634.

14. Gullett, J. C., Tillman, M. D., Gutierrez, G. M., & Chow, J. W. (2009). A biomechanical comparison of back and front squats in healthy trained individuals. *Journal of Strength and Conditioning Research*, 23(1), 284–292.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

15. Lorenzetti, S., Ostermann, M., Zeidler, F., Zimmer, P., Jentsch, L., List, R., Taylor, W. R., & Schellenberg, F. (2018). How to squat? Effects of various stance widths, foot placement angles and level of experience on knee, hip and trunk motion. *BMC Sports Science, Medicine and Rehabilitation*, 10(1), 14.

16. Kritz, M., Cronin, J., & Hume, P. (2009). The bodyweight squat: A movement screen for the squat pattern. *Strength & Conditioning Journal*, 31(1), 76–85.

17. Myer, G. D., Kushner, A. M., Brent, J. L., Schoenfeld, B. J., Hugentobler, J., Lloyd, R. S., Vermeil, A., Chu, D., Harbin, J., McGill, S. M., & Kraemer, W. J. (2014). The back squat: A proposed assessment of functional deficits and technical factors that limit performance. *Strength & Conditioning Journal*, 36(6), 4–27.

18. Nuzzo, J. L., McCaulley, G. O., Cormie, P., Cavill, M. J., & McBride, J. M. (2008). Relationship between countermovement jump performance and multijoint isometric and dynamic tests of strength. *Journal of Strength and Conditioning Research*, 22(3), 699–707.

19. Stone, M. H., O'Bryant, H. S., & Garhammer, J. (1981). A hypothetical model for strength training. *Journal of Sports Medicine and Physical Fitness*, 21, 342–351.

20. Stone, M. H., Stone, M. E., & Sands, W. A. (2007). *Principles and Practice of Resistance Training*. Human Kinetics.

21. Suchomel, T. J., Nimphius, S., & Stone, M. H. (2016). The importance of muscular strength in athletic performance. *Sports Medicine*, 46(10), 1419–1449.

22. Comfort, P., McMahon, J. J., & Suchomel, T. J. (2018). Optimizing squat performance: Biomechanical considerations. *Strength & Conditioning Journal*, 40(6), 68–79.

23. Robertson, D. G., Caldwell, G. E., Hamill, J., Kamen, G., & Whittlesey, S. (2013). *Research Methods in Biomechanics*. Human Kinetics.

24. Winter, D. A. (2009). *Biomechanics and Motor Control of Human Movement*. Wiley.

25. Zatsiorsky, V. M., & Kraemer, W. J. (2006). *Science and Practice of Strength Training*. Human Kinetics.

26. Enoka, R. M. (2008). *Neuromechanics of Human Movement*. Human Kinetics.

27. McBride, J. M., Blow, D., Kirby, T. J., Haines, T. L., Dayne, A. M., & Triplett, N. T. (2009). Relationship between maximal squat strength and sprint performance. *Journal of Strength and Conditioning Research*, 23(6), 1633–1636.

28. Wretenberg, P., Feng, Y., & Arborelius, U. (1996). High- and low-bar squatting techniques during weight-training. *Medicine & Science in Sports & Exercise*, 28(2), 218–224.

29. Sinclair, J., Taylor, P. J., & Hobbs, S. J. (2015). The influence of different squat techniques on lower extremity joint loading. *Sports Biomechanics*, 14(3), 309–320.

30. Schoenfeld, B. J., Contreras, B., Vigotsky, A., Ogborn, D., Fontana, F., & Tiryaki-Sonmez, G. (2016). Differential effects of heavy versus moderate loads on measures of strength and hypertrophy. *Journal of Strength and Conditioning Research*, 30(7), 1801–1807.

JMMBS
JOURNAL OF MOVEMENT MECHANICS & BIOMECHANICS SCIENCE
Research, reviews, and methodological work in biomechanics, movement mechanics, rehabilitation, and performance science

31. McKean, M. R., Dunn, P. K., & Burkett, B. J. (2010). The lumbar and sacrum movement pattern during the back squat exercise. *Journal of Strength and Conditioning Research*, 24(10), 2731–2741.

32. Clark, D. R., Lambert, M. I., & Hunter, A. M. (2012). Muscle activation in the loaded free barbell squat. *Journal of Strength and Conditioning Research*, 26(5), 1169–1178.

33. Chiu, L. Z., & Schilling, B. K. (2005). A primer on weightlifting: From sport to sports training. *Strength & Conditioning Journal*, 27(1), 42–48.

34. Brown, S. R., Helms, E. R., & Storey, A. G. (2019). The biomechanics of the squat exercise: Implications for performance and injury prevention. *Strength & Conditioning Journal*, 41(2), 1–13.

35. Vigotsky, A. D., Halperin, I., Lehman, G. J., Trajano, G. S., & Vieira, T. M. (2018). Interpreting signal amplitudes in surface electromyography studies in sport and rehabilitation sciences. *Frontiers in Physiology*, 8, 985.